

TECHNICAL RESOURCE

BENTOMAT®

PANEL & ROLL SPECIFICATIONS

PANEL SPECIFICATIONS			
PRODUCT	DIMENSIONS WIDTH X LENGTH ¹	AREA	EFFECTIVE AREA
BENTOMAT® ST	15 ft x 150 ft (4.6 m x 45.7 m)	2,250 ft ² (209 m ²)	2,145 ft ² (200 m ²)
BENTOMAT® SDN	14.5 ft x 150 ft (4.4 m x 45.7 m)	2,175 ft ² (202 m ²)	2,071 ft ² (193 m ²)
BENTOMAT® DN	14.5 ft x 150 ft (4.4 m x 45.7 m)	2,175 ft ² (202 m ²)	2,071 ft ² (193 m ²)
BENTOMAT® STM	15 ft x 200 ft (4.6 m x 60.9 m)	3,000 ft ² (279 m ²)	2,871 ft ² (267 m ²)
BENTOMAT® CL	15 ft x 150 ft (4.6 m x 45.7 m)	2,250 ft ² (209 m ²)	2,070 ft ² (193 m ²)
BENTOMAT® CLT	15 ft x 150 ft (4.6 m x 45.7 m)	2,250 ft ² (209 m ²)	2,070 ft ² (193 m ²)
BENTOMAT® 600 CL	15 ft x 150 ft (4.6 m x 45.7 m)	2,250 ft ² (209 m ²)	2,070 ft ² (193 m ²)
BENTOMAT® 200R	15 ft x 150 ft (4.6 m x 45.7 m)	2,250 ft ² (209 m ²)	2,145 ft ² (200 m ²)

¹ Roll widths and lengths have a tolerance of $\pm 1\%$.

ROLL SPECIFICATIONS			
PRODUCT	DIMENSIONS WIDTH X LENGTH (AVERAGE)	NOMINAL WEIGHT	ROLLS/TRUCKLOAD
BENTOMAT® ST	16 ft x 24 in (4.9 m x 610 mm)	2,650 lbs (1204 kg)	17 rolls per truckload
BENTOMAT® SDN	16 ft x 24 in (4.9 m x 610 mm)	2,650 lbs (1204 kg)	16 rolls per truckload
BENTOMAT® DN	16 ft x 24 in (4.9 m x 610 mm)	2,700 lbs (1227 kg)	16 rolls per truckload
BENTOMAT® STM	16 ft x 25 in (4.9 m x 635 mm)	2,500 lbs (1130 kg)	18 rolls per truckload
BENTOMAT® CL	16 ft x 25 in (4.9 m x 635 mm)	2,750 lbs (1250 kg)	15 rolls per truckload
BENTOMAT® CLT	16 ft x 26 in (4.9 m x 660 mm)	2,950 lbs (1340 kg)	15 rolls per truckload
BENTOMAT® 600 CL	16 ft x 25 in (4.9 m x 635 mm)	2,700 lbs (1227 kg)	16 rolls per truckload
BENTOMAT® 200R	16 ft x 24 in (4.9 m x 610 mm)	2,650 lbs (1204 kg)	17 rolls per truckload

Unloading and handling equipment for all GCL products:

- Spreader bar and core pipe: Spreader bar 17 ft (5.2 m) long; core pipe 20 ft (6.1 m) long, nominal pipe size, XXH.
- A solid 3.5 in. (90 mm) O.D. x 14.5 ft (4.4 m) solid steel pipe stinger attachment for a forklift.
- Slings: 2 Polyester slings are required, approximately 12 ft (3.7 m) long x 2 in (50 mm) wide each.
- Vehicle needed: Front end loader or forklift (are typical).

Standard Roll Specifications:

- Packaging: U.V. resistant polyethylene sleeve.

LAST UPDATED MARCH 2011

IMPORTANT: The information contained herein supersedes all previous printed versions, and is believed to be accurate and reliable. For the most up-to-date information, please visit www.CETCO.com. CETCO accepts no responsibility for the results obtained through application of this product. CETCO reserves the right to update information without notice.



www.CETCO.com

2870 Forbs Avenue Hoffman Estates, IL 60192
847.851.1800 | 800.527.9948